

Flexible waterproofing slurry

AQUAFIN®-1K PREMIUM

Rapid and stylish
progression.

The new one component, flexible premium grade waterproofing slurry, which allows the early installation of tiled finishes, is extremely simple and smooth to apply. Perfect for quickly and easily achieving your objectives and with economical consumption rates.

Problems Solved.



www.schomburg.com

 **SCHOMBURG**

Smooth to work –
better progress.
Workable for 60 minutes.
Tiling after 3 to 4 hours.

Rapid, smooth, economical, versatile: The latest one component and flexible premium grade waterproofing slurry unites all the properties you would wish for in a mineral-based waterproofing slurry. The solution to achieving your goal simply and economically.



60 minutes
working time!



Install tiles
after 3-4 hours!



Rapid application,
confident results!

Flexible waterproofing slurry **AQUAFIN®-1K-PREMIUM**

1 component, flexible, mineral-based waterproofing slurry for bonded waterproofing. Ready to receive fully tiled finishes after a short period of time.

Smooth in application with an extremely high yield.



Technical Data

Basis	Pre-blended mortar, polymer-mortar combination
Pot life*	Approx. 60 minutes
Substrate/Material/ Application temperature	+5°C to +30°C
Application	Hand, Mechanical equipment
Ready for use	Tiles and slabs can be installed after 3-4 hours
Packaging	15 kg polythene bag

* at +23°C and 50% relative humidity

Material demand **

Consumption	Approx. 1.25 kg powder per m ² /mm/ dry film thickness
-------------	--

** Increased material consumption on uneven substrates is not taken into consideration.




Areas of application

Bonded waterproofing layer:

- For assured and economical waterproofing underneath tiles, where impermeability to water over longer periods or under constant exposure is required.

Properties

- One component
- Rapid setting
- Ready for the installation of tiles and slabs after only 3 to 4 hours
- Very good to trowel and smooth off
- Simple economical application
- Can be brushed, trowelled or sprayed with suitable equipment
- Flexible and crack-bridging
- Vapour permeable, resistant to frost, UV, ageing
- For interior and exterior use



SCHOMBURG GmbH & Co. KG
AquaFinstrasse 2-8
D-32760 Detmold (Germany)
phone +49-5231-953-00
fax +49-5231-953-108
email export@schomburg.de
www.schomburg.com



 **SCHOMBURG**