Page 1/8

### Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.10.2022 Version number 1 Revision: 13.10.2022

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier
- · Trade name: THERMOPAL-ULTRA
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use SU19 Building and construction work
- · Application of the substance / the mixture Construction chemicals
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

SCHOMBURG GmbH & Co. KG

Aquafinstr. 2-8 D-32760 Detmold Germany

-----

Tel: ++49 (0)5231/953-00 Fax: ++49 (0)5231/953-123 email: info@schomburg.de web: www.schomburg.de

· Informing department:

**Product Safety Department** 

Tel: ++49 (0)5231/953-770 email: SDB@schomburg.de

#### **SECTION 2: Hazards identification**

- 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



corrosion

Eye Dam. 1 H318 Causes serious eye damage.



Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H335 May cause respiratory irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

- · Hazard pictograms GHS05, GHS07
- Signal word Danger
- · Hazard-determining components of labelling:

Cement, portland, chemicals

Flue dust, portland cement

· Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

(Contd. on page 2)

(Contd. of page 1)

### Safety data sheet according to 1907/2006/EC, Article 31

Version number 1 Revision: 13.10.2022 Printing date 13.10.2022

Trade name: THERMOPAL-ULTRA

· Precautionary statements

Avoid breathing dust/fume/gas/mist/vapours/spray.

P261 Wear protective gloves / eye protection / face protection. P280

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

Dispose of contents/container in accordance with local/regional/national/ P501

international regulations.

Additional information:

EUH208 Contains Cement, portland, chemicals, Flue dust, portland cement. May produce an allergic reaction.

2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT**: Not applicable. · vPvB: Not applicable.

#### **SECTION 3: Composition/information on ingredients**

3.2 Chemical characterisation: Mixtures

· Description: Product based on cement and mineral filler.

· Dangerous components:

CAS: 65997-15-1 Cement, portland, chemicals 10-25%

EINECS: 266-043-4 📀 Eye Dam. 1, H318; 🕔 Skin Irrit. 2, H315; Skin Sens. 1B, H317;

STOT SE 3, H335

CAS: 68475-76-3 Flue dust, portland cement 2.5-10%

**Additional information** 

The chromate content in cement is less than 2 ppm so that the labelling with H317 is not applicable (1907/2006/EG, Annex XVII (47)).

For the wording of the listed hazard phrases refer to section 16.

#### **SECTION 4: First aid measures**

4.1 Description of first aid measures

#### · General information

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Personal protection for the First Aider.

It is possible to choke in case of vomiting in unconsciousness.

Bring unconscious persons into a stable position on side.

Keep the respiratory tract free (remove dentures and vomiting).

Check the pulse. In case of heart failure you have to make a cardiac massage. In case of stoppage of breathing: artificial respiration.

Take up a doctor immediately!

· After inhalation Supply fresh air or oxygen; call for doctor.

#### · After skin contact

Instantly wash with water and soap and rinse thoroughly.

Wash with water and soap.

After contact, clean the skin mechanical and rinse with water and soap.

· After eye contact Rinse opened eye for several minutes under running water. Then consult doctor.

#### · After swallowing

Drink copious amounts of water and provide fresh air. Instantly call for doctor.

Show the packaging or the label to the doctor.

(Contd. on page 3)

## Safety data sheet

according to 1907/2006/EC, Article 31

Version number 1

Trade name: THERMOPAL-ULTRA

Printing date 13.10.2022

(Contd. of page 2)

Revision: 13.10.2022

· 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

#### **SECTION 5: Firefighting measures**

- 5.1 Extinguishing media
- · Suitable extinguishing agents Use fire fighting measures that suit the environment.
- · For safety reasons unsuitable extinguishing agents Cement
- 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained breathing apparatus.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations. Follow the emergency-plan.

#### **SECTION 6: Accidental release measures**

 6.1 Personal precautions, protective equipment and emergency procedures Bring persons out of danger.

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow product to reach sewage system or water bodies.

Inform respective authorities in case product reaches water or sewage system.

The product may not leak out in sewerage system, stretch of water or soil.

6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Pick up the product mechanically, avoid dust formation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

#### **SECTION 7: Handling and storage**

7.1 Precautions for safe handling

Prevent formation of dust.

Keep away from children.

- Information about protection against explosions and fires: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- Requirements to be met by storerooms and containers: No special requirements.
- Information about storage in one common storage facility:

Please follow the rules of the VCI-Storage-Concept for chemicals.

- Further information about storage conditions: Keep container tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

#### **SECTION 8: Exposure controls/personal protection**

- 8.1 Control parameters
- · Additional information about design of technical systems:

It must be possible to wash the skin in the working area.

Eye-wash bottle must be available.

(Contd. on page 4)

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.10.2022 Version number 1 Revision: 13.10.2022

Trade name: THERMOPAL-ULTRA

(Contd. of page 3)

#### · Components with critical values that require monitoring at the workplace:

#### 65997-15-1 Cement, portland, chemicals (10-25%)

WEL Long-term value: 10\* 4\*\* mg/m³ \*inhalable dust \*\*respirable dust

- · Additional information: The lists that were valid during the compilation were used as basis.
- 8.2 Exposure controls
- Personal protective equipment

#### General protective and hygienic measures

The usual precautionary measures should be adhered to in handling the chemicals.

Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments.

Vacuum clean contaminated clothing. Do not blow or brush off contamination.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

Do not eat, drink or smoke while working.

Use skin protection cream for preventive skin protection.

Be sure to clean skin thoroughly after work and before breaks.

#### Breathing equipment:

In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.

#### Protection of hands:

Do not reuse one-way-gloves

Hand Protection: Nitril-rubber-latex-gloves.

In case of wearing synthetic protective gloves use cotton-gloves as underwear.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

Mechanical protective glove with a coating of PVC or nitrile

Suitable protective gloves have been determined for activities with products containing cement (GISCODES ZP1). Suitable are e.g:

Ampri: SolidSafety Cut 081101 / SolidSafety Tough 081201 / SolidSafetyTough Dots 081202

Ansell: Flexitril L27 / Fleximax 27 or 35 / Hylite / Nitrotough N210 / Sol-Knit

KCL: Sahara / Gobi / Nitex

MAPA: Duo-Mix 405 / Enduro 328 / Stansolv AK 22 / Titanlite 397 / Titansuperlite

UVEX: uvex Profi Ergo XG 20 / uvex phynomic pro

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye protection: Tightly sealed safety glasses.
- · Body protection:

Use an Overall of heavy cotton or non-returnable Tyvek/Saranex 23 P vleece.

Contaminated protection clothes must be cleaned carefully before reuse.

- GE

### Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.10.2022 Version number 1 Revision: 13.10.2022

Trade name: THERMOPAL-ULTRA

(Contd. of page 4)

SECTION 9: Physical and chemical pro	perties
• 9.1 Information on basic physical and • General Information	chemical properties
· Appearance: Form:	Powder
Colour:	grey
· Smell:	Characteristic
· Odour threshold:	Not determined.
· pH-value at 20 °C:	11.4 (1%)
<ul> <li>Change in condition</li> <li>Melting point/freezing point:</li> <li>Initial boiling point and boiling range</li> </ul>	Not determined : not apply
· Flash point:	Not applicable
· Inflammability (solid, gaseous)	Not determined.
· Decomposition temperature:	Not determined.
· Self-inflammability:	Product is not selfigniting.
· Explosive properties:	Product is not explosive.
<ul> <li>Critical values for explosion:</li> <li>Lower:</li> <li>Upper:</li> </ul>	Not determined. Not determined.
· Steam pressure:	Not applicable.
· Density	bulk density
· Settled apparent density · Relative density · Vapour density · Evaporation rate	1-1.3 kg/m³ Not determined. Not applicable. Not applicable.
· Solubility in / Miscibility with Water:	miscible
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity: dynamic: kinematic:	Not applicable. Not applicable.
9.2 Other information	No further relevant information available.

### **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known

C D

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.10.2022 Version number 1 Revision: 13.10.2022

Trade name: THERMOPAL-ULTRA

(Contd. of page 5)

#### **SECTION 11: Toxicological information**

- 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values that are relevant for classification:

#### 68475-76-3 Flue dust, portland cement

Oral LD50 >1,848 mg/kg (rats) (OECD 422)
Dermal LD50 >2,000 mg/kg (rats) (OECD 402)
Inhalative LC50/4 h >6.04 mg/l (rats) (OECD 436)

- · Primary irritant effect:
- · Skin corrosion/irritation

The product has an irritate-effect.

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye damage.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause respiratory irritation.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

#### **SECTION 12: Ecological information**

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water.

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

#### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.10.2022 Version number 1 Revision: 13.10.2022

Trade name: THERMOPAL-ULTRA

(Contd. of page 6)

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleaning agent: Water, if necessary with cleaning agent.

SECTION 14: Transport information	
· 14.1 UN-Number · ADR, IMDG, IATA	Void
· 14.2 UN proper shipping name · ADR, IMDG, IATA	Void
· 14.3 Transport hazard class(es)	
· ADR, ADN, IMDG, IATA · Class	Void
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Not applicable.
14.7 Transport in bulk according to And of Marpol and the IBC Code	nex II Not applicable.
· UN "Model Regulation":	Void

#### **SECTION 15: Regulatory information**

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

#### Department issuing data specification sheet:

Department EHS (Environment-Health-Safety)

Environment protection department.

· Contact: Department EHS (Environment-Health-Safety)

#### · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 8)

Page 8/8

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.10.2022 Version number 1 Revision: 13.10.2022

Trade name: THERMOPAL-ULTRA

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1B: Skin sensitisation – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

\* Data compared to the previous version altered.

(Contd. of page 7)