

# Declaration of Performance

according Annex III oft he Regulation (EU) No. 305/2011

#### for the product

## **ASODUR-LE**

205797

1. Unique identification code of the product type: EN 1504-2 Principle 5.1

EN13813

2. Identification: batch no.: see packaging of the product

3. Intended use: EN 1504-2

Survis protection product / coating

EN 13813

Synthetic resin screed for use internally

in buildings.

4. Manufacturer: Schomburg GmbH & Co. KG

Aquafinstrasse 2-8 32760 Detmold

5. Authorized representative: not relevant

6. System or systems of assessment and verification of constancy of performance

of the construction product as:

System 4

System 3 reaction to fire

8. Notified test laboratory:

The notified body MPA NRW identification number 0432 performed the determination


of the class regarding reaction to fire on the basis of product testing under system 3 and issued: **test report No 230004942-6** 

## 9. Declared performance:

#### Table 1:

7.

| Essential characteristics                                | Performance       | Harmonised technical specification |
|--|-------------------|------------------------------------|
| Capillary water absorption and water permeability        | NPD               |                                    |
| Pull off test for determination of the adhesive strength | ≥ 1,5 (1,0) N/mm² | EN 1504-2:2004                     |
| Abrasive resistance                                      | NPD               | 1                                  |



| Strong chemical attack resistance | NPD                          |  |
|-----------------------------------|------------------------------|--|
| Shock strength                    | NPD                          |  |
| Reaction to fire                  | Class Cfl s1                 |  |
| Dangerous substances              | According 5.3<br>(EN 1504-2) |  |

#### Table 2:

| Essential characteristics       | Performance              | Harmonised technical specification |
|---------------------------------|--------------------------|------------------------------------|
| Reaction to fire                | Class C <sub>fl</sub> s1 |                                    |
| Release of corrosive substances | SR                       | DIN EN 13813: 2002                 |
| Wear resistance                 | NPD                      |                                    |
| Adhesive strength               | ≥ B1,5                   |                                    |
| Shock strength                  | NPD                      | ]                                  |

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

### Signed for and on behalf of the manufacturer by:

Michael Hölscher, technician (name and function)

Detmold, 17.06.2013

This declaration of performance was created electronically. It is valid without manual signature.

The current material safety data sheet and technical data sheet is downloadable under

http://www.schomburg-ics.de/en/Materials safety Data Sheet MSDS-datenblaetter.html

or

http://www.schomburg-ics.de/en/Technical\_Data\_Sheet-datenblaetter.html