

# ASO®-R005

Cleaning concentrate for tiles, clinker bricks and concrete blocks



Material number	Contents	Unit of quantity	Packaging	Colour
206400004	25	L	Canister	Colourless
206400003	10	L	Canister	Colourless
206400002	5	L	Canister	Colourless
206400001	1	L	Bottle	Colourless

## Product features

- concentrate
- Solvent free

## Advantages

- leaves no residue
- dissolves cement residue, concrete and mortar residue, lime secretions and chalky efflorescence

## Areas of application

- For removing efflorescence, lime, cement and mortar residues
- suitable for exposed masonry

## Technical Data

### Material properties

Product components	1 component system
Base material	organic acid
Consistency	liquid
Water dilutable	yes

### Application

Substrate/application temperature	from 5 °C to 30 °C
-----------------------------------	--------------------

## ASO<sup>®</sup>-R005

### Application technology

#### Aids/tools

- Clean mixing bucket
- Broad paint brush
- Nylon brush
- Spray equipment
- Occupational safety equipment

### Suitable substrate

- Concrete
- Masonry work
- Clinker
- Tiles

### Usage

#### Application

1. The grout nets must be adequately pre-dampened before applying ASO<sup>®</sup>-R005.
2. Only apply ASO<sup>®</sup>-R005 diluted with clean water (depending on the degree of contamination and the strength of the stone deposit from 1:3 to 1:10).
3. Structurally sealed containers must be ventilated.
4. For old or stubborn contaminants, repeat the cleaning process.
5. The dissolved substances must be rinsed off immediately with suitably clear water.
6. The effect of ASO<sup>®</sup>-R005 starts immediately after contact with the substances to be dissolved. This is visible due to strong, foamy carbon dioxide formation.
7. Use of a nylon brush and warm water can considerably improve the cleaning effect.
8. Cleaning is done from top to bottom.

### Storage conditions

#### Storage

Frost-free, cool and dry. 24 months in the original container. Promptly use opened container.

### Disposal

Product leftovers can be disposed of in accordance with disposal code AVW 07 01 99.

### Notes

- Protect surfaces that are not to be treated from the effects of ASO<sup>®</sup>-R005!
- The stone and tile manufacturers' suitability and design recommendations must be observed.
- Protect metals from corrosion!
- For application, never use metal containers or metal devices!
- To prevent colour changes in the substrate to be treated, to assess tolerance and determine consumption, a pretest is always necessary!

GISCODE: GG40

The rights of the buyer with regard to the quality of our materials are based on our terms and conditions of sale and delivery. Our technical advice team will be happy to advise you in the case of requirements that exceed the scope of the application described here. In order to be binding, a legally binding written confirmation is required. The product description does not release the user from a duty of care. Lay a test area in the event of uncertainty. This version becomes invalid in the event of a new version being issued.