

ASO[®]-SB

Self-adhesive fabric tape with cut-resistant effect



Material number	Length	Width, article	Material strength	Packaging	Colour
201616001	10 m	50 mm	approx. 0.65 mm	Roll	Beige with SCHOMBURG logo

Product features

- Cut protection tape
- Multiple skin-layered
- Self-adhesive

Advantages

Easy to process

Areas of use/bonded waterproofing

- As protection using joint tape systems in the expansion, movement and edge connecting joints areas
- As protection for the joint tape system to prevent cutting during maintenance work on elastic movement joints

Technical Data

Material properties

Product components	Roll goods
Base material	self-adhesive fabric tape made of polyamide and aramid, with release liner
Width of cut protection zone	approx. 40 mm
UV-resistance as per DIN EN ISO 4892-2	200 hours
Temperature resistance	- 5 + 60 °C

Application

Consumption	approx. 1 m per m
-------------	-------------------

Application technology

Aids/tools

- Pressure roller
- Craft knife
- Folding ruler
- Scissors/knife

ASO[®]-SB

Usage

Application

1. The waterproofing materials must have hardened/set.
2. Remove the peel-off film from ASO[®]-SB and bond centrally in the area of the movement and connecting joint.

Storage conditions

Storage

Cool, dry, protected from sunlight. Min. 24 months in the original container.

Disposal

Product leftovers can be disposed of in household waste.

Notes

Remove adhesive strips from any existing interfaces of the joint tape roll. Establish the connection area overlapping.

Planning, inspection of substrates and building site circumstances, laying, grouting and subsequent care of the work must be done in accordance with the relevant DIN standards and recognised rules of technology (e.g. the ZDB sheets of the Zentralverband Deutsches Baugewerbe e.V.) in the latest version.

The rights of the buyer with regard to the quality of our materials are based on our terms and conditions of sale and delivery. Our technical advice team will be happy to advise you in the case of requirements that exceed the scope of the application described here. In order to be binding, a legally binding written confirmation is required. The product description does not release the user from a duty of care. Lay a test area in the event of uncertainty. This version becomes invalid in the event of a new version being issued.