



SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier
- Trade name: **ASODUR-GBM (B-Komp.)(INDUFLOOR-IB 1225 (B-Komp.))**
- Article number: 205751B
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
No further relevant information available.
- Application of the substance / the mixture Epoxy coating
- 1.3 Details of the supplier of the safety data sheet
- **Manufacturer/Supplier:**
SCHOMBURG GmbH & Co. KG
Aquafinstr. 2-8
D-32760 Detmold
Germany

Tel: ++49 (0)5231/953-00
Fax: ++49 (0)5231/953-123
email: info@schomburg.de
web: www.schomburg.de
- **Informing department:**
Product Safety Department

Tel: ++49 (0)5231/953-193
Fax: ++49 (0)5231/953-106
email: guido.herfort@schomburg.de

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- **Classification according to Regulation (EC) No 1272/2008**
-  GHS05 corrosion
- Skin Corr. 1B H314 Causes severe skin burns and eye damage.
- Eye Dam. 1 H318 Causes serious eye damage.
-  GHS07
- Acute Tox. 4 H332 Harmful if inhaled.
- Skin Sens. 1 H317 May cause an allergic skin reaction.
- Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.
- 2.2 Label elements
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms** GHS05, GHS07
- **Signal word** Danger
- **Hazard-determining components of labelling:**
Benzyl alcohol

(Contd. on page 2)

Trade name: ASODUR-GBM (B-Komp.)(INDUFLOOR-IB 1225 (B-Komp.))

(Contd. of page 1)

4,4'-Isopropylidendiphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine
4,4'-Isopropylidendiphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane reaction products -phenylenbis (methylamine)
3-aminomethyl-3,5,5-trimethylcyclohexylamine

· **Hazard statements**

H332 Harmful if inhaled.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H412 Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

P260 Do not breathe dusts or mists.
P273 Avoid release to the environment.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Additional information:**

EUH071 Corrosive to the respiratory tract.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· **3.2 Chemical characterisation: Mixtures**

· **Description:** Hardener, aminformulation

· **Dangerous components:**

CAS: 100-51-6	Benzyl alcohol	25-50%
EINECS: 202-859-9	⚠ Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	
CAS: 38294-64-3	4,4'-Isopropylidendiphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine	25-50%
	⚠ Skin Corr. 1B, H314; Eye Dam. 1, H318; ⚠ Skin Sens. 1, H317; Aquatic Chronic 3, H412	
CAS: 113930-69-1	4,4'-Isopropylidendiphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane reaction products -phenylenbis (methylamine)	10-25%
	⚠ Skin Corr. 1B, H314; Eye Dam. 1, H318; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Sens. 1, H317	
CAS: 2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	2.5-10%
EINECS: 220-666-8	⚠ Skin Corr. 1B, H314; Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	

GB

(Contd. on page 3)

Trade name: **ASODUR-GBM (B-Komp.)(INDUFLOOR-IB 1225 (B-Komp.))**

(Contd. of page 2)

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· **General information**

Instantly remove any clothing soiled by the product.

It is possible to choke in case of vomiting in unconsciousness.

Bring unconscious persons into a stable position on side.

Keep the respiratory tract free (remove dentures and vomiting).

Check the pulse. In case of heart failure you have to make a cardiac massage. In case of stoppage of breathing: artificial respiration.

Take up a doctor immediately!

Personal protection for the First Aider.

· **After inhalation** Supply fresh air or oxygen; call for doctor.

· **After skin contact**

Instantly wash with water and soap and rinse thoroughly.

Change immediately contaminated clothes.

If symptoms appearance, call the doctor.

· **After eye contact** Rinse opened eye for several minutes under running water. Then consult doctor.

· **After swallowing**

Do not induce vomiting; instantly call for medical help.

Show the pack or the label to the doctor.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· **Suitable extinguishing agents** CO₂, extinguishing powder or water jet. Fight larger fires with water jet.

· 5.2 Special hazards arising from the substance or mixture

Formation of poisonous gases during heating or in fires.

· 5.3 Advice for firefighters

· **Protective equipment:** Wear self-contained breathing apparatus.

· **Additional information**

Follow the emergency-plan.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Burst- and explosion-danger by increasing pressure.

In case of fire chill the container with water spray.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Cleaning may be carried out only with skilled persons.

· **6.2 Environmental precautions:** Do not allow product to reach sewage system or water bodies.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding, inflammable material (sand, diatomite, acid binders, universal binder).

· 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

(Contd. on page 4)

Trade name: ASODUR-GBM (B-Komp.)(INDUFLOOR-IB 1225 (B-Komp.))

See Section 13 for information on disposal.

(Contd. of page 3)

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
 - Ensure good ventilation/exhaustion at the workplace.
 - Keep away from children.
 - Keep away from heat and direct sunlight.
 - Open and handle container with care.
 - Work with fresh air supply, keep doors and windows open.
- **Information about protection against explosions and fires:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
 - **Storage**
 - **Requirements to be met by storerooms and containers:**
 - Do not leave open containers.
 - Do not store in common rooms.
 - No special requirements.
 - **Information about storage in one common storage facility:**
 - Store away from foodstuffs.
 - Please follow the rules of the VCI-Storage-Concept for chemicals.
 - **Further information about storage conditions:**
 - Keep container tightly sealed.
 - Store in a locked cabinet and out of the reach of children.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical systems:**
 - It must be possible to wash the skin in the working area.
 - Eye-wash bottle must be available.
- **8.1 Control parameters**
- **Components with critical values that require monitoring at the workplace:**
 - The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists that were valid during the compilation were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment**
- **General protective and hygienic measures**
 - Avoid contact with the eyes and skin.
 - The usual precautionary measures should be adhered to in handling the chemicals.
 - Do not take thinner to clean the skin.
 - Be sure to clean skin thoroughly after work and before breaks.
- **Breathing equipment:** Not required.
- **Protection of hands:** Hand Protection: Nitril-rubber-latex-gloves.
- **Material of gloves**
 - Nitril-rubber-latex-gloves II R: Thickness $\geq 0,5\text{mm}$; Break through time ≥ 480 min
- **Penetration time of glove material**
 - The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:** Safety glasses

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.11.2019

Version number 30

Revision: 07.11.2019

Trade name: **ASODUR-GBM (B-Komp.)(INDUFLOOR-IB 1225 (B-Komp.))**

(Contd. of page 4)

- **Body protection:**
Protective work clothing.
Contaminated protection clothes must be cleaned carefully before reuse.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Fluid
Colour:	Colourless
Smell:	Amine-like

· pH-value: Not determined.

· Change in condition

Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined

· Flash point: 94 °C

· Self-inflammability: Product is not selfigniting.

· Explosive properties: Product is not explosive.

· Critical values for explosion:

Lower:	Not determined.
Upper:	Not determined.

· Steam pressure: Not determined.

· Density at 20 °C 1.04 g/cm³

· Solubility in / Miscibility with

Water: miscible

· Viscosity:

dynamic at 20 °C:	145 mPas
kinematic:	Not determined.

· 9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

· Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions Exothermic reaction

· 10.4 Conditions to avoid No further relevant information available.

· 10.5 Incompatible materials: Acids

· 10.6 Hazardous decomposition products: No dangerous decomposition products known

GB

(Contd. on page 6)

Trade name: **ASODUR-GBM (B-Komp.)(INDUFLOOR-IB 1225 (B-Komp.))**

(Contd. of page 5)

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity

Harmful if inhaled.

· LD/LC50 values that are relevant for classification:

100-51-6 Benzyl alcohol

Oral LD50 1,570 mg/kg (rats)

Inhalative LC50 11 mg/l

2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine

Oral LD50 1,030 mg/kg (rats) (OECD 401)

Dermal LD50 1,840 mg/kg (rabbit)
>2,000 mg/kg (rats)

· Primary irritant effect:

· Skin corrosion/irritation

Causes severe skin burns and eye damage.

· Serious eye damage/irritation

Causes serious eye damage.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

· Additional toxicological information: Sensitizing

· CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

· **Germ cell mutagenicity** Based on available data, the classification criteria are not met.

· **Carcinogenicity** Based on available data, the classification criteria are not met.

· **Reproductive toxicity** Based on available data, the classification criteria are not met.

· **STOT-single exposure** Based on available data, the classification criteria are not met.

· **STOT-repeated exposure** Based on available data, the classification criteria are not met.

· **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine

LC50/96h 110 mg/l (Leuciscus idus)

EC50 (48h) 23 mg/l (Daphnia magna)

EC/10/18h 1,120 mg/l (Pseudomas putida)

ERC50 >50 mg/l (Scenedesmus subspicatus)

· **12.2 Persistence and degradability** No further relevant information available.

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil** No further relevant information available.

· Additional ecological information:

· General notes:

Water hazard class 2 (Self-assessment): hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system.

· 12.5 Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.11.2019

Version number 30

Revision: 07.11.2019

Trade name: **ASODUR-GBM (B-Komp.)(INDUFLOOR-IB 1225 (B-Komp.))**

(Contd. of page 6)

· **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**· **Recommendation**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Must be specially treated under adherence to official regulations.

Transfer to a permitted waste disposal institution.

· **European waste catalogue**

08 00 00 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS

08 01 00 wastes from MFSU and removal of paint and varnish

08 01 11 waste paint and varnish containing organic solvents or other dangerous substances

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

· **Recommended cleaning agent:** Water, if necessary with cleaning agent.

SECTION 14: Transport information

· **14.1 UN-Number**· **ADR, IMDG, IATA**

UN2735

· **14.2 UN proper shipping name**· **ADR**

2735 AMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine), ISOPHORONEDIAMINE)

· **IMDG, IATA**

AMINES, LIQUID, CORROSIVE, N.O.S. (4,4'-Isopropylidendiphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine, 4,4'-Isopropylendiphenol, oligomeric reaction products with 1-chlorine-2,3-epoxypropane reaction products -phenylenebis (methylamine))

· **14.3 Transport hazard class(es)**· **ADR, IMDG, IATA**· **Class**

8 Corrosive substances.

· **Label**

8

· **14.4 Packing group**· **ADR, IMDG, IATA**

II

· **14.5 Environmental hazards:**· **Marine pollutant:**

No

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.11.2019

Version number 30

Revision: 07.11.2019

Trade name: **ASODUR-GBM (B-Komp.)(INDUFLOOR-IB 1225 (B-Komp.))**

(Contd. of page 7)

<ul style="list-style-type: none"> · 14.6 Special precautions for user · Kemler Number: · EMS Number: · Stowage Category 	<p>Warning: Corrosive substances. 80 F-A,S-B A</p>
<ul style="list-style-type: none"> · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code 	Not applicable.
<ul style="list-style-type: none"> · Transport/Additional information: 	
<ul style="list-style-type: none"> · ADR · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category · Tunnel restriction code 	<p>1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml 2 E</p>
<ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) 	<p>1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml</p>
<ul style="list-style-type: none"> · UN "Model Regulation": 	<p>UN2735, AMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine), ISOPHORONEDIAMINE), 8, III</p>

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **National regulations**
- **Water hazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
- **Department issuing data specification sheet:** Environment protection department.

(Contd. on page 9)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 07.11.2019

Version number 30

Revision: 07.11.2019

Trade name: ASODUR-GBM (B-Komp.)(INDUFLOOR-IB 1225 (B-Komp.))

(Contd. of page 8)

· **Contact:** Mr. Guido Herfort

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· *** Data compared to the previous version altered.**

GB