Revision: 05.01.2017



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 05.01.2017

Version number 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: ASODUR-IH (A-Komp.)(INDUFLOOR -VK-Injekt (A-Komp.))

· Article number: 205769

 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.

· Application of the substance / the mixture Epoxy resin

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

SCHOMBURG GmbH & Co. KG

Aquafinstr. 2-8 D-32760 Detmold

Germany

·

Tel: ++49 (0)5231/953-00 Fax: ++49 (0)5231/953-123 email: info@schomburg.de web: www.schomburg.de

· Informing department:

Product Safety Department

Tel: ++49 (0)5231/953-193 Fax: ++49 (0)5231/953-106

email: guido.herfort@schomburg.de

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

· 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- · Hazard pictograms GHS07, GHS09
- Signal word Warning
- · Hazard-determining components of labelling:

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700) bisphenol-F-epoxy resin

oxirane, mono[(C12-14-alkyloxy)methyl] derivs

· Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 2)

according to 1907/2006/EC, Article 31

Printing date 05.01.2017 Version number 8 Revision: 05.01.2017

Trade name: ASODUR-IH (A-Komp.)(INDUFLOOR -VK-Injekt (A-Komp.))

(Contd. of page 1)

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P363 Wash contaminated clothing before reuse.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

Additional information:

Contains epoxy constituents. May produce an allergic reaction.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- Description: Preparation based on Bisphenol-A-Epichlorhydrin resin molecular weight ≤ 700.
- · Dangerous components:

CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number 50-100% NLP: 500-033-5 average molecular weight ≤ 700)

Aquatic Chronic 2, H411; \(\frac{1}{2} \) Skin Irrit. 2, H315; Eye Irrit. 2, H319;

Skin Sens. 1, H317

CAS: 9003-36-5 bisphenol-F-epoxy resin 10-25%

Škin Šens. 1, H317

CAS: 8002-09-3 Pine oil C 30 2.5-10%

Skin Irrit. 2, H315

CAS: 68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs 2.5-10%

EINECS: 271-846-8 Skin Irrit. 2, H315; Skin Sens. 1, H317

SECTION 4: First aid measures

4.1 Description of first aid measures

· General information

Personal protection for the First Aider.

It is possible to choke in case of vomiting in unconsciousness.

Bring unconscious persons into a stable position on side.

Keep the respiratory tract free (remove dentures and vomiting).

Check the pulse. In case of heart failure you have to make a cardiac massage. In case of stoppage of breathing: artificial respiration.

Take up a doctor immediately!

- After inhalation Supply fresh air or oxygen; call for doctor.
- · After skin contact Instantly wash with water and soap and rinse thoroughly.
- · After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

- · After swallowing Do not induce vomiting; instantly call for medical help.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)

according to 1907/2006/EC, Article 31

Printing date 05.01.2017 Version number 8 Revision: 05.01.2017

Trade name: ASODUR-IH (A-Komp.)(INDUFLOOR -VK-Injekt (A-Komp.))

(Contd. of page 2)

 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam. Use fire fighting measures that suit the environment.

· 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained breathing apparatus.
- · Additional information Follow the emergency-plan.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow product to reach sewage system or water bodies.
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep containers tightly sealed.

Keep away from heat and direct sunlight.

Use only in well ventilated areas.

Work with fresh air supply, keep doors and windows open.

Keep away from children.

Do not store open containers.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

- 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- · Requirements to be met by storerooms and containers:

No special requirements.

Do not store in common rooms.

· Information about storage in one common storage facility:

Please follow the rules of the VCI-Storage-Concept for chemicals.

- Further information about storage conditions: Keep container tightly sealed.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7 MSDS.
- · 8.1 Control parameters
- · Components with critical values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

(Contd. on page 4)

according to 1907/2006/EC, Article 31

Printing date 05.01.2017 Version number 8 Revision: 05.01.2017

Trade name: ASODUR-IH (A-Komp.)(INDUFLOOR -VK-Injekt (A-Komp.))

(Contd. of page 3)

- · Additional information: The lists that were valid during the compilation were used as basis.
- 8.2 Exposure controls
- Personal protective equipment
- General protective and hygienic measures

The usual precautionary measures should be adhered to in handling the chemicals.

Instantly remove any soiled and impregnated garments. Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

- · Breathing equipment: Not required.
- · Protection of hands: Hand Protection: Nitril-rubber-latex-gloves.
- Material of gloves

Butyl rubber II R: Thickness ≥ 0,5mm; Break through time ≥ 480 min

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye protection: Safety glasses
- · Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid

Colour: According to product specification

· Smell: Characteristic

· pH-value at 20 °C: 8.4

· Change in condition

Melting point/freezing point: Not determined Initial boiling point and boiling range: Not determined

· Flash point: 120 ℃

· **Self-inflammability:** Product is not selfigniting.

• Explosive properties: Product is not explosive.

· Density at 20 °C 1.1 g/cm³

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix

· Viscosity:

dynamic at 20 °C: 1000 mPas

9.2 Other information
 No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 5)

according to 1907/2006/EC, Article 31

Printing date 05.01.2017 Version number 8 Revision: 05.01.2017

Trade name: ASODUR-IH (A-Komp.)(INDUFLOOR -VK-Injekt (A-Komp.))

(Contd. of page 4)

10.6 Hazardous decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values that are relevant for classification:

25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)

Oral LD50 >5000 mg/kg (rats)

Dermal LD50 >2000 mg/kg (rats)

9003-36-5 bisphenol-F-epoxy resin

Oral LD50 >10000 mg/kg (rats)

Dermal LD50 >2000 mg/kg (rats)

68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs

Oral LD50 34600 mg/kg (rats)

Dermal LD50 >23800 mg/kg (rabbit)

- · Primary irritant effect:
- Skin corrosion/irritation

Causes skin irritation.

· Serious eve damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met. Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)

LC50 (96h) 2 mg/l (rainbow trout)

EC50 (48h) 1.7 mg/l (Daphnia sp.)

EC50 (48h) 1.7 mg/l (Daphnia magna)

NOEC 0.3 mg/l (Daphnia magna)

9003-36-5 bisphenol-F-epoxy resin

LC50/96h 2.54 mg/l (Leuciscus idus) EC50 2.55 mg/l (Daphnia magna) ERC50 1.8 mg/l (algae toxicity)

68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs

EC50 (48h) 1-10 mg/l (Daphnia magna)

EC50 1-10 mg/l (Daphnia magna)

· 12.2 Persistence and degradability No further relevant information available.

(Contd. on page 6)

according to 1907/2006/EC, Article 31

Printing date 05.01.2017 Version number 8 Revision: 05.01.2017

Trade name: ASODUR-IH (A-Komp.)(INDUFLOOR -VK-Injekt (A-Komp.))

(Contd. of page 5)

- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · European waste catalogue
- 07 00 00 WASTES FROM ORGANIC CHEMICAL PROCESSES
- 07 02 00 wastes from the MFSU of plastics, synthetic rubber and man-made fibres
- 07 02 04 other organic solvents, washing liquids and mother liquors
- 07 00 00 WASTES FROM ORGANIC CHEMICAL PROCESSES
- 07 02 00 wastes from the MFSU of plastics, synthetic rubber and man-made fibres
- 07 02 99 wastes not otherwise specified
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

| 14.1 UN-Number ADR, IMDG, IATA | UN3082 |
|-----------------------------------|--|
| 14.2 UN proper shipping name | |
| ADR | 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol A-(epichlorhydrin); epoxy resin(number average molecular weight<700), oxirane, mono[(C12-14-alkyloxy)methyl] derivs) |
| IMDG | ENVIRONMENTALLY HAZARDOUS SUBSTANC LIQUID, N.O.S. (bisphenol A-(epichlorhydrin); epoxy resin(number average molecular weight<700), oxirane, mono[(C12-14-alkyloxy) methyl] derivs), MARINE POLLUTANT |
| IATA | ENVIRONMENTALLY HAZARDOUS SUBSTANCI LIQUID, N.O.S. (bisphenol A-(epichlorhydrin); epoxy resin(number average molecular weight<700), oxirane, mono[(C12-14-alkyloxy) methyl] derivs) |

according to 1907/2006/EC, Article 31

Version number 8 Revision: 05.01.2017 Printing date 05.01.2017

Trade name: ASODUR-IH (A-Komp.)(INDUFLOOR -VK-Injekt (A-Komp.))

(Contd. of page 6)

· 14.3 Transport hazard class(es)

· ADR, IMDG, IATA



· 14.4 Packing group

· Class 9 Miscellaneous dangerous substances and articles.

· Label

· ADR, IMDG, IATA

Ш

14.5 Environmental hazards:

· Marine pollutant: Symbol (fish and tree) Special marking (ADR): Symbol (fish and tree) Special marking (IATA): Symbol (fish and tree)

· 14.6 Special precautions for user Warning: Miscellaneous dangerous substances and

articles.

· Kemler Number: 90 · EMS Number: F-A.S-F

14.7 Transport in bulk according to Annex II

of Marpol and the IBC Code Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ) 5L · Transport category 3 · Tunnel restriction code Ε

· UN "Model Regulation": UN3082, ENVIRONMENTALLY HAZARDOUS

SUBSTANCE, LIQUID, N.O.S. (bisphenol A-(epichlorhydrin); epoxy resin(number average molecular weight<700), oxirane, mono[(C12-14-

alkyloxy)methyl] derivs), 9, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations
- · Water hazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

(Contd. on page 8)

according to 1907/2006/EC, Article 31

Printing date 05.01.2017 Version number 8 Revision: 05.01.2017

Trade name: ASODUR-IH (A-Komp.)(INDUFLOOR -VK-Injekt (A-Komp.))

(Contd. of page 7)

H411 Toxic to aquatic life with long lasting effects.

· Department issuing data specification sheet: Environment protection department.

· Contact: Mr. Guido Herfort

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the

International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

* Data compared to the previous version altered.

GB