

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.10.2019 Version number 6 Revision: 01.10.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

· Trade name: ASODUR-LE (A-Komponente)

· Article number: 205199

· 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.

· Application of the substance / the mixture Epoxy coating

1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

SCHOMBURG GmbH & Co. KG

Aquafinstr. 2-8 D-32760 Detmold Germany

Tel: ++49 (0)5231/953-00 Fax: ++49 (0)5231/953-123 email: info@schomburg.de web: www.schomburg.de

· Informing department:

Product Safety Department

Tel: ++49 (0)5231/953-193 Fax: ++49 (0)5231/953-106

email: guido.herfort@schomburg.de

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- Hazard pictograms GHS07, GHS09
- · Signal word Warning
- · Hazard-determining components of labelling:

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700) 1,6-bis(2,3-ethoxypropoxy)hexane

Hazard statements

H315 Causes skin irritation.

(Contd. on page 2)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.10.2019 Version number 6

Printing date 01.10.2019 Version

Trade name: ASODUR-LE (A-Komponente)

(Contd. of page 1)

Revision: 01.10.2019

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

Description:

Solvent- free preparation based on Bisphenol-A-Epichlorhydrin resin molecular weight < 700.

Dangerous components:

CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average 50-100%

NLP: 500-033-5 molecular weight ≤ 700)

Aquatic Chronic 2, H411; (Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin

Sens. 1, H317

CAS: 16096-31-4 1,6-bis(2,3-ethoxypropoxy)hexane

(1) Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic

3, H412

· Additional information Contains epoxide-compounds. Note the index of the manufacturer.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- · General information

Personal protection for the First Aider.

It is possible to choke in case of vomiting in unconsciousness.

Bring unconscious persons into a stable position on side.

Keep the respiratory tract free (remove dentures and vomiting).

Check the pulse. In case of heart failure you have to make a cardiac massage. In case of stoppage of breathing: artificial respiration.

Take up a doctor immediately!

- · After inhalation Supply fresh air; consult doctor in case of symptoms.
- · After skin contact

Change immediately contaminated clothes.

Instantly wash with water and soap and rinse thoroughly.

Don't use solvents to clean the skin.

- · After eye contact Rinse opened eye for several minutes under running water. Then consult doctor.
- After swallowing

Do not induce vomiting; instantly call for medical help.

Show the pack or the label to the doctor.

(Contd. on page 3)

25-50%

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.10.2019 Version number 6 Revision: 01.10.2019

Trade name: ASODUR-LE (A-Komponente)

(Contd. of page 2)

· 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents CO2, extinguishing powder or water jet. Fight larger fires with water jet.
- 5.2 Special hazards arising from the substance or mixture

Formation of poisonous gases during heating or in fires.

- 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained breathing apparatus.
- Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Avoid eye- and skin contact.

Wear protective equipment. Keep unprotected persons away.

Do not breath in vapour.

Keep away from ignition sources

6.2 Environmental precautions:

Do not allow product to reach sewage system or water bodies.

Build barriers with sand, soil or other sealings.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding, inflammable material (sand, diatomite, acid binders, universal binder).

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep containers tightly sealed.

Work with fresh air supply, keep doors and windows open.

Keep away from children.

Keep away from heat and direct sunlight.

Avoid splashes. Do not spray on hot surfaces.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

- 7.2 Conditions for safe storage, including any incompatibilities
- Storage
- · Requirements to be met by storerooms and containers:

Store in cool location.

Do not leave open containers.

Do not store in common rooms.

Information about storage in one common storage facility:

Store away from foodstuffs.

(Contd. on page 4)

(Contd. of page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.10.2019 Version number 6 Revision: 01.10.2019

Trade name: ASODUR-LE (A-Komponente)

Please follow the rules of the VCI-Storage-Concept for chemicals.

Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed containers.

Protect from frost.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical systems:

It must be possible to wash the skin in the working area.

Eye-wash bottle must be available.

- 8.1 Control parameters
- · Components with critical values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the compilation were used as basis.
- 8.2 Exposure controls
- · Personal protective equipment
- · General protective and hygienic measures

Before starting work and after each break apply low-fat or fat-free skin cream on all uncovered parts of the body.

Clean skin only with cleaning agent especially for epoxy resin.

Don't use solvent for skin cleaning!

Clean clothes which are contaminate with epoxi resin before unsing again.

The usual precautionary measures should be adhered to in handling the chemicals.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

- · Breathing equipment: Not required.
- · Protection of hands: Hand Protection: Nitril-rubber-latex-gloves.
- · Material of gloves

Nitril-rubber-latex-gloves II R: Thickness ≥ 0,5mm; Break through time ≥ 480 min

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye protection: Safety glasses
- · Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties
- · General Information
- Appearance:

Form: Liquid Colour: Colourless

· **Smell:** Weak, characteristic

· Change in condition

Melting point/freezing point: Not determined

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.10.2019 Version number 6 Revision: 01.10.2019

Trade name: ASODUR-LE (A-Komponente)

		(Contd. of page 4
Initial boiling point and boiling r	ange: > 200 °C	
· Flash point:	130 °C	
· Ignition temperature:	235 °C	
· Self-inflammability:	Product is not selfigniting.	
· Explosive properties:	Product is not explosive.	
· Steam pressure at 20 °C:	0.1 hPa	
· Density at 20 °C	1.12 g/cm³	
· Solubility in / Miscibility with Water:	Unsoluble	
Viscosity: dynamic at 20 °C: 9.2 Other information	1588 mPas No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions Reacts violently with oxidizing agents
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: Can react with acid and oxidizing agends.
- 10.6 Hazardous decomposition products:

În case of heating dangerous decomposition products can be arise.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values that are relevant for classification:

25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700)

Oral LD50 >5000 mg/kg (rats)
Dermal LD50 >2000 mg/kg (rats)

16096-31-4 1,6-bis(2,3-ethoxypropoxy)hexane

Oral LD50 1400 mg/kg (rabbit)

2900 mg/kg (rats)

Inhalative LC50/4 h >100 mg/l (Maus)

- · Primary irritant effect:
- Skin corrosion/irritation

Causes skin irritation.

- Serious eye damage/irritation
- Causes serious eye irritation.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.

(Contd. on page 6)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.10.2019 Version number 6 Revision: 01.10.2019

Trade name: ASODUR-LE (A-Komponente)

(Contd. of page 5)

- · Additional toxicological information: Sensitizing
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)

LC50 (96h) 2 mg/l (rainbow trout)

EC50 (48h) 1.7 mg/l (Daphnia sp.)

EC50 (48h) 1.7 mg/l (Daphnia magna)

NOEC 0.3 mg/l (Daphnia magna)

- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- Recommendation

Transfer to a permitted waste diposal institution.

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Cured materials which mixed with epoxy resin can put to the houshold-rubbish, after consulting the waste diposal.

- · European waste catalogue
- 07 00 00 WASTES FROM ORGANIC CHEMICAL PROCESSES
- 07 02 00 wastes from the MFSU of plastics, synthetic rubber and man-made fibres
- 07 02 99 wastes not otherwise specified
- 08 00 00 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
- 08 01 00 wastes from MFSU and removal of paint and varnish
- 08 01 99 wastes not otherwise specified

(Contd. on page 7)

Printing date 01.10.2019 Version number 6 Revision: 01.10.2019

Trade name: ASODUR-LE (A-Komponente)

(Contd. of page 6)

- · Uncleaned packagings:
- Recommendation:

Empty Containers with solid product rests can be supplied for recycling. Empty Containers including fluid product rests are hazardous waste. Disposal must be made according to official regulations.

14.1 UN-Number ADR, IMDG, IATA	UN3082
	010002
14.2 UN proper shipping name ADR	3082 ENVIRONMENTALLY HAZARDOUS
	SUBSTANCE, LIQUID, N.O.S. (bisphenol A-
	(epichlorhydrin); epoxy resin(number average
	molecular weight<700), oxirane, mono[(C12-14- alkyloxy)methyl] derivs)
IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANC
	LIQUID, N.O.S. (bisphenol A-(epichlorhydrin); epo
	resin(number average molecular weight<700),
	oxirane, mono[(C12-14-alkyloxy)methyl] derivs), MARINE POLLUTANT
IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANC
	LIQUID, N.O.S. (bisphenol A-(epichlorhydrin); eporesin(number average molecular weight<700),
	oxirane, mono[(C12-14-alkyloxy)methyl] derivs)
· 14.3 Transport hazard class(es)	
· 14.3 Transport hazard class(es) · ADR, IMDG, IATA	
ADR, IMDG, IATA	9 Miscellaneous dangerous substances and articl
. , ,	9 Miscellaneous dangerous substances and article 9
ADR, IMDG, IATA Class Label 14.4 Packing group	9
ADR, IMDG, IATA Class Label 14.4 Packing group	
Class Label 14.4 Packing group ADR, IMDG, IATA	9 III
ADR, IMDG, IATA Class	9 III Yes
Class Label 14.4 Packing group ADR, IMDG, IATA 14.5 Environmental hazards: Marine pollutant:	9 III Yes Symbol (fish and tree)
Class Label 14.4 Packing group ADR, IMDG, IATA 14.5 Environmental hazards: Marine pollutant: Special marking (ADR):	9 III Yes
Class Label 14.4 Packing group ADR, IMDG, IATA	9 III Yes Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree)
Class Label 14.4 Packing group ADR, IMDG, IATA 14.5 Environmental hazards: Marine pollutant: Special marking (ADR): Special marking (IATA): 14.6 Special precautions for user	9 III Yes Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree) Warning: Miscellaneous dangerous substances at articles.
ADR, IMDG, IATA Class Label 14.4 Packing group ADR, IMDG, IATA 14.5 Environmental hazards: Marine pollutant: Special marking (ADR): Special marking (IATA): 14.6 Special precautions for user Kemler Number:	9 III Yes Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree) Warning: Miscellaneous dangerous substances at articles. 90
Class Label 14.4 Packing group ADR, IMDG, IATA 14.5 Environmental hazards: Marine pollutant: Special marking (ADR): Special marking (IATA): 14.6 Special precautions for user	9 III Yes Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree) Warning: Miscellaneous dangerous substances at articles. 90

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.10.2019 Version number 6 Revision: 01.10.2019

Trade name: ASODUR-LE (A-Komponente)

	(Contd. of page 7)	
· ADR · Limited quantities (LQ) · Transport category · Tunnel restriction code	5L 3 E	
UN "Model Regulation":	UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol A-(epichlorhydrin); epoxy resin(number average molecular weight<700), oxirane, mono[(C12-14-alkyloxy)methyl] derivs), 9, III	

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations
- · Water hazard class:

Water hazard class 2 (Self-assessment): hazardous for water.

The classification based on german instructions.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

- · Department issuing data specification sheet: Environment protection department.
- · Contact: Mr. Guido Herfort
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation - Category 1

(Contd. on page 9)

Page 9/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.10.2019 Version number 6 Revision: 01.10.2019

Trade name: ASODUR-LE (A-Komponente)

(Contd. of page 8)

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

* Data compared to the previous version altered.

⊇R -