



Declaration of Performance

according Annex III of the Regulation (EU) No 305/2011
amended by Commissions delegated Regulation (EU) No 574/2014

for the product

INDUFLEX-PS

20 6414

1. **Unique identification code of the product type:** EN 14188-2 sl M
2. **Intended use:** Joint sealant for fuel-resistant joints in concrete surfaces and other traffic areas
3. **Manufacturer:** Schomburg GmbH & Co. KG
Aquafinstrasse 2-8
32760 Detmold
4. **System or systems of assessment and verification of constancy of performance of the construction product as:** System: 4
5. **Harmonised standard** EN 14188-2:2004
6. **Notified test laboratory:** not relevant
7. **Declared performance :**

Essantial characteristic	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification
Fire reaction	class E	System 4	EN 14188-2:2004
Adhesion strength	No failure at -20°C ≤ 0,6 MPa		
Adhesion and Tensile Strength	Tensile Modulus at 100% Elongation at 23°C ≥ 0,15 MPa at -20°C ≤ 0,6 MPa		
Recovering capability	≥ 70%		
Permanence of Water Impermeability	passed		
Adhesion and Tensile Strength after storage in liquid chemicals of class B,C and D	No failure		
Resistance against hydrolysis	passed		
Artificial Weathering by UV exposure	passed		
Flame resistance	passed		



The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Michael Hölscher, technical service surface protection
(name and function)

Detmold, 28.10.2016

*This declaration of performance was created electronically.
It is valid without manual signature.*

The current material safety data sheet and technical data sheet is downloadable under

http://www.schomburg.com/de/en/downloads/datasheets/materials_safety_data_sheet/d

or

http://www.schomburg.com/de/en/downloads/datasheets/technical_data_sheet/d