






**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

- **1.1 Product identifier**
- **Trade name: Asodur-K 900 (A-Komp.)**
- **Article number:** 205070
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the mixture** Epoxy coating
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
SCHOMBURG GmbH  
Aquafinstr. 2-8  
D-32760 Detmold  
Germany  
-----  
Tel: ++49 (0)5231/953-00  
Fax: ++49 (0)5231/953-123  
email: info@schomburg.de  
web: www.schomburg.de
- **Informing department:**  
Product Safety Department  
  
Tel: ++49 (0)5231/953-193  
Fax: ++49 (0)5231/953-106  
email: guido.herfort@schomburg.de

**SECTION 2: Hazards identification**

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
-  GHS09 environment  
  
Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.  
-----
-  GHS07  
  
Skin Irrit. 2            H315 Causes skin irritation.  
Eye Irrit. 2            H319 Causes serious eye irritation.  
Skin Sens. 1            H317 May cause an allergic skin reaction.  
-----
- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**
-  Xi; Irritant  
R36/38: Irritating to eyes and skin.  
-----
-  Xi; Sensitising  
R43:            May cause sensitisation by skin contact.  
-----
-  N; Dangerous for the environment  
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- **Information concerning particular hazards for human and environment:**  
The product may not leak out in sewerage system, stretch of water or soil.  
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

(Contd. on page 2)

**Trade name: Asodur-K 900 (A-Komp.)**

(Contd. of page 1)

• **Classification system:**

The classification is in line with current EC lists. It is expanded, however, by information from technical literature and by information furnished by supplier companies.

• **2.2 Label elements**

• **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

• **Hazard pictograms** GHS07, GHS09

• **Signal word** Warning

• **Hazard-determining components of labelling:**

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)  
bisphenol-F-epoxy resin

1,6-bis(2,3-ethoxypropoxy)hexane

• **Hazard statements**

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

• **Precautionary statements**

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P363 Wash contaminated clothing before reuse.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

• **Additional information:**

Contains epoxy constituents. May produce an allergic reaction.

• **2.3 Other hazards**

• **Results of PBT and vPvB assessment**

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

**SECTION 3: Composition/information on ingredients**

• **3.2 Chemical characterisation: Mixtures**

• **Description:**

Solvent- free preparation based on Bisphenol-A-Epichlorhydrin resin molecular weight  $\leq$  700.

• **Dangerous components:**

CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700) 50-100%

NLP: 500-033-5

 Xi R36/38; Xi R43; N R51/53

 Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317

CAS: 38640-62-9 Diisopropylnaphtalene 10-25%


 Xn R65; N R51/53

 Asp. Tox. 1, H304; Aquatic Chronic 4, H413

CAS: 9003-36-5 bisphenol-F-epoxy resin 2.5-10%

NLP: 500-006-8

 Xi R36/38; Xi R43; N R51/53

 Aquatic Chronic 2, H411; Eye Irrit. 2, H319; Skin Sens. 1, H317

(Contd. on page 3)

**Trade name: Asodur-K 900 (A-Komp.)**

(Contd. of page 2)

CAS: 16096-31-4 1,6-bis(2,3-ethoxypropoxy)hexane 2.5-10%

☒ Xi R36/38; ☒ Xi R43  
R52/53

⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic  
Chronic 3, H412

- **Additional information** For the wording of the listed risk phrases refer to section 16.

#### SECTION 4: First aid measures

##### • 4.1 Description of first aid measures

##### • **General information**

Personal protection for the First Aider.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Personal protection for the First Aider.

It is possible to choke in case of vomiting in unconsciousness.

Bring unconscious persons into a stable position on side.

Keep the respiratory tract free (remove dentures and vomiting).

Check the pulse. In case of heart failure you have to make a cardiac massage. In case of stoppage of breathing: artificial respiration.

Take up a doctor immediately!

- **After inhalation** Supply fresh air or oxygen; call for doctor.

##### • **After skin contact**

Don't use solvents to clean the skin.

Instantly wash with water and soap and rinse thoroughly.

##### • **After eye contact**

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

##### • **After swallowing**

Do not induce vomiting; instantly call for medical help.

Show the pack or the label to the doctor.

##### • 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

##### • 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

#### SECTION 5: Firefighting measures

##### • 5.1 Extinguishing media

##### • **Suitable extinguishing agents**

CO<sub>2</sub>, extinguishing powder or water jet. Fight larger fires with water jet.

- **For safety reasons unsuitable extinguishing agents** Water with a full water jet.

##### • 5.2 Special hazards arising from the substance or mixture

Formation of poisonous gases during heating or in fires.

##### • 5.3 Advice for firefighters

- **Protective equipment:** Wear self-contained breathing apparatus.

##### • **Additional information**

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Follow the emergency-plan.

#### SECTION 6: Accidental release measures

##### • 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Avoid eye- and skin contact.

Do not breath in vapour.

Keep away from ignition sources

(Contd. on page 4)

**Trade name: Asodur-K 900 (A-Komp.)**

(Contd. of page 3)

Bring persons out of danger.

Wear protective equipment. Keep unprotected persons away.

- **6.2 Environmental precautions:** Do not allow product to reach sewage system or water bodies.

- **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding, inflammable material (sand, diatomite, acid binders, universal binder).

- **6.4 Reference to other sections**

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

## SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**

Keep containers tightly sealed.

Work with fresh air supply, keep doors and windows open.

Keep away from heat and direct sunlight.

Keep away from children.

- **Information about protection against explosions and fires:** No special measures required.

- **7.2 Conditions for safe storage, including any incompatibilities**

- **Storage**

- **Requirements to be met by storerooms and containers:** Do not leave open containers.

- **Information about storage in one common storage facility:**

Store away from foodstuffs.

Please follow the rules of the VCI-Storage-Concept for chemicals.

- **Further information about storage conditions:**

Protect from frost.

Keep container tightly sealed.

- **7.3 Specific end use(s)** No further relevant information available.

## SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical systems:**

It must be possible to wash the skin in the working area.

Eye-wash bottle must be available.

- **8.1 Control parameters**

- **Components with critical values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- **Additional information:** The lists that were valid during the compilation were used as basis.

- **8.2 Exposure controls**

- **Personal protective equipment**

- **General protective and hygienic measures**

Clean skin only with cleaning agent especially for epoxy resin.

Don't use solvent for skin cleaning!

Clean clothes which are contaminate with epoxi resin before unusing again.

The usual precautionary measures should be adhered to in handling the chemicals.

Instantly remove any soiled and impregnated garments.

Avoid contact with the eyes and skin.

Be sure to clean skin thoroughly after work and before breaks.

- **Breathing equipment:**

In not so good ventilated space the filter combination A2B2E2K1HgP3RD is to be used.

- **Protection of hands:** Hand Protection: Nitril-rubber-latex-gloves.

- **Material of gloves**

Butyl rubber II R: Thickness  $\geq 0,5\text{mm}$ ; Break through time  $\geq 480\text{ min}$

(Contd. on page 5)

**Trade name: Asodur-K 900 (A-Komp.)**

(Contd. of page 4)

- **Penetration time of glove material**  
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:** Safety glasses
- **Body protection:**  
Protective work clothing.  
Contaminated protection clothes must be cleaned carefully before reuse.

### SECTION 9: Physical and chemical properties

#### • 9.1 Information on basic physical and chemical properties

##### • General Information

##### • Appearance:

Form:	Liquid
Colour:	Colourless
Smell:	Type specific

##### • Change in condition

Melting point/Melting range:	Not determined
Boiling point/Boiling range:	Not determined

• **Flash point:** Not applicable

• **Self-inflammability:** Product is not selfigniting.

• **Danger of explosion:** Product is not explosive.

• **Density at 20 °C** 1.13 g/cm<sup>3</sup>

##### • Solubility in / Miscibility with

**Water:** Not miscible or difficult to mix

##### • Viscosity:

**dynamic at 20 °C:** 1500 mPas

• **9.2 Other information** No further relevant information available.

### SECTION 10: Stability and reactivity

#### • 10.1 Reactivity

#### • 10.2 Chemical stability

#### • **Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

#### • 10.3 Possibility of hazardous reactions

Reacts violently with oxidizing agents

Reacts with strong acids and oxidizing agents

• **10.4 Conditions to avoid** No further relevant information available.

• **10.5 Incompatible materials:** Can react with acid and oxidizing agents.

#### • 10.6 Hazardous decomposition products:

În case of heating dangerous decomposition products can be arise.

### SECTION 11: Toxicological information

#### • 11.1 Information on toxicological effects

##### • Acute toxicity:

##### • **LD/LC50 values that are relevant for classification:**

**25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)**

Oral LD50 >5000 mg/kg (rats)

(Contd. on page 6)

**Trade name: Asodur-K 900 (A-Komp.)**

(Contd. of page 5)

Dermal LD50 &gt;2000 mg/kg (rats)

**38640-62-9 Diisopropylnaphtalene**

Oral LD50 &gt;3900 mg/kg (rats)

Dermal LD50 &gt;4500 mg/kg (rats)

Inhalative LC 50 5.64 mg/l (rats)

**9003-36-5 bisphenol-F-epoxy resin**

Oral LD50 &gt;5000 mg/kg (rats)

**16096-31-4 1,6-bis(2,3-ethoxypropoxy)hexane**

Oral LD50 1400 mg/kg (rabbit)

2900 mg/kg (rats)

Inhalative LC50/4 h &gt;100 mg/l (Maus)

• **Primary irritant effect:**• **on the skin:** Irritant for skin and mucous membranes.• **on the eye:** Irritant effect.• **Sensitisation:** Sensitization possible by skin contact.• **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version:

Irritant

Sensitizing

**SECTION 12: Ecological information**• **12.1 Toxicity**• **Aquatic toxicity:****25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)**

EC50 (24h) 3.6 mg/l (Daphnia magna)

LC50 (96h) 1.5 mg/l (rainbow trout)

**38640-62-9 Diisopropylnaphtalene**

EC0 (72h) 0.15 mg/l (algae toxicity)

(48h) 0.16 mg/l (Daphnia (acute) toxicity)

LC 0 (96h) 0.5 mg/l (fish toxicity)

**9003-36-5 bisphenol-F-epoxy resin**

EC50 2 mg/l (Daphnia (acute) toxicity)

LC50/96h 2 mg/l (fish toxicity)

• **12.2 Persistence and degradability****25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)**

301B (Mod. Sturm) 12 % (-)

• **12.3 Bioaccumulative potential** No further relevant information available.• **12.4 Mobility in soil** No further relevant information available.• **Ecotoxicological effects:**• **Remark:** Harmful to fish• **Additional ecological information:**• **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

Harmful to aquatic organisms

(Contd. on page 7)

**Trade name: Asodur-K 900 (A-Komp.)**


(Contd. of page 6)

- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **European waste catalogue**  
17 00 00 CONSTRUCTION AND DEMOLITION WASTES (INCLUDING EXCAVATED SOIL FROM CONTAMINATED SITES)  
17 02 00 wood, glass and plastic  
17 02 03 plastic
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

### SECTION 14: Transport information

- |   |   |
|---|---|
| • <b>14.1 UN-Number</b>   | UN3082  |
| • <b>ADR, IMDG, IATA</b>  | UN3082  |
| • <b>14.2 UN proper shipping name</b>   | 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol A-(epichlorhydrin); epoxy resin(number average molecular weight<700), Diisopropylnaphthalin-Isomere)              |
| • <b>ADR</b>  | 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol A-(epichlorhydrin); epoxy resin(number average molecular weight<700), Diisopropylnaphthalin-Isomere)              |
| • <b>IMDG</b>   | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol A-(epichlorhydrin); epoxy resin(number average molecular weight<700), Diisopropylnaphthalin-Isomere), MARINE POLLUTANT |
| • <b>IATA</b>   | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol A-(epichlorhydrin); epoxy resin(number average molecular weight<700), Diisopropylnaphthalin-Isomere)                   |
| • <b>14.3 Transport hazard class(es)</b>  |   |
| • <b>ADR, IMDG, IATA</b>  |   |
|  |   |
| • <b>Class</b>  | 9 Miscellaneous dangerous substances and articles.  |
| • <b>Label</b>  | 9   |
| • <b>14.4 Packing group</b>   | III   |
| • <b>ADR, IMDG, IATA</b>  | III   |
| • <b>14.5 Environmental hazards:</b>  |   |
| • <b>Marine pollutant:</b>  | Yes<br>Symbol (fish and tree)   |

(Contd. on page 8)



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 04.02.2015

Version number 11

Revision: 04.02.2015

**Trade name: Asodur-K 900 (A-Komp.)**

(Contd. of page 7)

· <b>Special marking (ADR):</b>	Symbol (fish and tree)
· <b>Special marking (IATA):</b>	Symbol (fish and tree)
· <b>14.6 Special precautions for user</b>	Warning: Miscellaneous dangerous substances and articles.
· <b>Kemler Number:</b>	90
· <b>EMS Number:</b>	F-A,S-F
· <b>14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>ADR</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Transport category</b>	3
· <b>Tunnel restriction code</b>	E
· <b>UN "Model Regulation":</b>	UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol A-(epichlorhydrin); epoxy resin(number average molecular weight<700), Diisopropylnaphtalene), 9, III

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **National regulations**
- **Water hazard class:**  
Water hazard class 2 (Self-assessment): hazardous for water.  
The classification based on german instructions.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
    - H304 May be fatal if swallowed and enters airways.
    - H315 Causes skin irritation.
    - H317 May cause an allergic skin reaction.
    - H319 Causes serious eye irritation.
    - H411 Toxic to aquatic life with long lasting effects.
    - H412 Harmful to aquatic life with long lasting effects.
    - H413 May cause long lasting harmful effects to aquatic life.
  - R36/38 Irritating to eyes and skin.
  - R43 May cause sensitisation by skin contact.
  - R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
  - R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
  - R65 Harmful: may cause lung damage if swallowed.
- **Department issuing data specification sheet:** Environment protection department.
  - **Contact:** Mr. Guido Herfort

(Contd. on page 9)

GB



**Trade name: Asodur-K 900 (A-Komp.)**

(Contd. of page 8)

• **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

Aquatic Chronic 4: Hazardous to the aquatic environment - Chronic Hazard, Category 4

• **\* Data compared to the previous version altered.**