Revision: 04.03.2015



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.03.2015

Version number 7

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

· Trade name: SOLOFLEX

· Article number: 205430

- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- Application of the substance / the mixture Tile adhesive
- · 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: SCHOMBURG GmbH

Aquafinstr. 2-8 D-32760 Detmold Germany

Tel: ++49 (0)5231/953-00 Fax: ++49 (0)5231/953-123 email: info@schomburg.de web: www.schomburg.de

 Informing department: **Product Safety Department**

Tel: ++49 (0)5231/953-193 Fax: ++49 (0)5231/953-106

email: guido.herfort@schomburg.de

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H335 May cause respiratory irritation.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Xi; Irritant

R37/38-41: Irritating to respiratory system and skin. Risk of serious damage to eyes.

Classification system:

The classification is in line with current EC lists. It is expanded, however, by information from technical literature and by information furnished by supplier companies.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- · Hazard pictograms GHS05, GHS07
- · Signal word Danger
- · Hazard-determining components of labelling:

Cement, portland, chemicals

· Hazard statements

H315 Causes skin irritation.

(Contd. on page 2)

according to 1907/2006/EC, Article 31

Printing date 04.03.2015 Version number 7 Revision: 04.03.2015

Trade name: SOLOFLEX

(Contd. of page 1)

H318 Causes serious eye damage. H335 May cause respiratory irritation.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

· Description: Product based on cement and mineral filler.

Dangerous components:

CAS: 65997-15-1 Cement, portland, chemicals EINECS: 266-043-4 ★ Xi R37/38-41; ★ Xi R43

25-50%

Eye Dam. 1, H318; **(**) Skin Irrit. 2, H315; STOT SE 3, H335

· Additional information

The chromate content in cement is less than 2 ppm so that the rating of the relevant phrase no. 43 is not applicable.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- · General information Personal protection for the First Aider.
- · After inhalation Supply fresh air; consult doctor in case of symptoms.
- · After skin contact Instantly wash with water and soap and rinse thoroughly.
- · After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

- · After swallowing Drink copious amounts of water. Avert vomiting. Instantly call for doctor.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents

Product is not inflammable.

Use fire fighting measures that suit the environment.

5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- 5.3 Advice for firefighters
- **Protective equipment:** Wear self-contained breathing apparatus.

(Contd. on page 3)

according to 1907/2006/EC, Article 31

Printing date 04.03.2015 Version number 7 Revision: 04.03.2015

Trade name: SOLOFLEX

· Additional information Follow the emergency-plan.

(Contd. of page 2)

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Avoid causing dust.

Avoid eye- and skin contact.

Wear protective clothing.

- 6.2 Environmental precautions: Do not allow product to reach sewage system or water bodies.
- · 6.3 Methods and material for containment and cleaning up:

Pick up the product mechanically, avoid dust formation.

6.4 Reference to other sections

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

See Section 7 for information on safe handling

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Prevent formation of dust.

Keep away from children.

- Information about protection against explosions and fires: No special measures required.
- 7.2 Conditions for safe storage, including any incompatibilities
- Storage
- · Requirements to be met by storerooms and containers: No special requirements.
- · Information about storage in one common storage facility:

Please follow the rules of the VCI-Storage-Concept for chemicals.

- · Further information about storage conditions: Protect from humidity and keep away from water.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical systems:

It must be possible to wash the skin in the working area.

Eye-wash bottle must be available.

No further data; see item 7 MSDS.

- · 8.1 Control parameters
- · Components with critical values that require monitoring at the workplace:

65997-15-1 Cement, portland, chemicals (25-50%)

WEL Long-term value: 10* 4** mg/m³

*inhalable dust **respirable dust

- · Additional information: The lists that were valid during the compilation were used as basis.
- 8.2 Exposure controls
- · Personal protective equipment
- General protective and hygienic measures

The usual precautionary measures should be adhered to in handling the chemicals.

Be sure to clean skin thoroughly after work and before breaks.

Instantly remove any soiled and impregnated garments.

Avoid contact with the eyes and skin.

- · Breathing equipment: Use respiratory protective equipment at formation of dust.
- · Protection of hands: Hand Protection: Nitril-rubber-latex-gloves.
- · Material of gloves

Butyl rubber II R: Thickness ≥ 0.5 mm; Break through time ≥ 480 min

(Contd. on page 4)

according to 1907/2006/EC, Article 31

Printing date 04.03.2015 Version number 7 Revision: 04.03.2015

Trade name: SOLOFLEX

(Contd. of page 3)

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Safety glasses

· Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

· Appearance:

Form: Powder Colour: Grey

· Smell: Weak, characteristic

· Change in condition

Melting point/Melting range: Not determined Boiling point/Boiling range: Not determined

· Flash point: Not applicable

· **Self-inflammability:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive.

· **Density** not determine

· Settled apparent density 1,370 kg/dm³

· Solubility in / Miscibility with

Water: Fully miscible

• 9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

544-17-2 Calciumformiat

Oral LD50 3050 mg/kg (rats)
Dermal LD50 >2000 mg/kg (rats)
Inhalative LC50/4 h >0.67 mg/l (rats)

- · Primary irritant effect:
- · on the skin: Irritant for skin and mucous membranes.
- · on the eye: Irritant effect.
- · Sensitisation: Sensitization possible by skin contact.

(Contd. on page 5)

according to 1907/2006/EC, Article 31

Printing date 04.03.2015 Version number 7 Revision: 04.03.2015

Trade name: SOLOFLEX

· Additional toxicological information:

(Contd. of page 4)

The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version:

Irritant

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity:

544-17-2 Calciumformiat

EC50 >1000 mg/l (bacterial toxicity)

EC50 (48h) >1000 mg/l (Daphnia magna)

LC 0 (96h) 1000 mg/l (Brachydanio rerio)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · European waste catalogue
- 10 00 00 WASTES FROM THERMAL PROCESSES
- 10 12 00 wastes from manufacture of ceramic goods, bricks, tiles and construction products
- 10 12 03 particulates and dust
- 17 00 00 CONSTRUCTION AND DEMOLITION WASTES (INCLUDING EXCAVATED SOIL FROM CONTAMINATED SITES)
- 17 01 00 concrete, bricks, tiles and ceramics
- 17 01 01 concrete
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleaning agent: Water, if necessary with cleaning agent.

14.1 UN-Number	
· ADR	Void
· 14.2 UN proper shipping name · ADR	Void
· 14.3 Transport hazard class(es)	
· ADR	
· Class	Void

(Contd. on page 6)

according to 1907/2006/EC, Article 31

Printing date 04.03.2015 Version number 7 Revision: 04.03.2015

Trade name: SOLOFLEX

	(Contd. of page 5)
· 14.4 Packing group · ADR	Void
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Not applicable.
14.7 Transport in bulk according to Annex of MARPOL73/78 and the IBC Code	II Not applicable.
· Transport/Additional information:	Not dangerous according to the above specifications.

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- National regulations
- · Water hazard class:

Water hazard class 1 (Self-assessment): slightly hazardous for water.

The classification based on german instructions.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H335 May cause respiratory irritation.

R37/38 Irritating to respiratory system and skin.

- R41 Risk of serious damage to eyes.
- R43 May cause sensitisation by skin contact.
- · Department issuing data specification sheet: Environment protection department.
- · Contact: Mr. Guido Herfort
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

· * Data compared to the previous version altered.

GB