



# ASOCRET-M30

## Water repellent multi-purpose mortar

Reactive drying for rapid construction progress  
even with challenging climatic conditions.

**Problems solved.**



# One for all – all in one!


## Water repellent multi-purpose mortar with up to 35% lower consumption.

Coved fillet mortar, blocking render, smoothing compound and repair mortar. Each application usually requires different products but not with us. We have **ASOCRET-M30**, the only renovation mortar, which combines all four products in one!

And **ASOCRET-M30** can do even more. The very lightweight product with smooth workability as well as up to 35% greater coverage speaks volumes for this renovation mortar with universal application. And furthermore, the building programme is not delayed as the areas can be overcoated after only approx. 3 hours. This offers the contractor real additional value in their daily work.

### ASOCRET-M30

- For interior and exterior areas
- Rapid setting
- Water impermeable
- Coved fillet mortar
- Sulfate resistant
- For thicknesses from 3–30 mm in one application
- Very smooth application
- High sag resistance
- Quickly ready to overcoat
- Almost shrinkage free
- Hand and machine processing

	
SCHOMBURG GmbH & Co. KG Aquafinstraße 2 – 8 D-32760 Detmold 15 2 05539	
DIN EN 998-1: 2010-12 <b>ASOCRET-M30</b> Normal plaster	
Compressive strength	CS IV
Capillary water absorption, category	W2
Water vapor permeability coefficient, (μ)	≤ 25
Tensile strength 28d	≥ 0.5 N/mm <sup>2</sup>
Fracture appearance	A
Thermal conductivity, λ10, dry, tabulated average value (P = 50 %), DIN EN 1745	< 0.67
Reaction to fire	A1
Durability (Frost resistance)	Resistant in case of handling according to the technical data sheet

### Application Data

Pot life*	approx. 30 minutes
Overcoat after*	approx. 3 hours
Flexural strength after 28 days	approx. 5.0 N/mm <sup>2</sup>
Compressive strength after 28 days	approx. 20.0 N/mm <sup>2</sup>
Water vapor permeability coefficient w24	< 0.1 kg/m <sup>2</sup> × h <sup>0.5</sup>
Packaging	6 kg and 25 kg plastic bag
Consumption surface levelling	approx. 1.4 kg/m <sup>2</sup> /mm thickness
Consumption mineral-based coved fillets	approx. 3.0 kg/m

\* The values refer to +23 ° C and 50% relative humidity.



### ASOCRET-M30 & AQUAFIN-RB400

Complete and reliable waterproofing with just two products!



### ATTENTION NEW!

Cementitious covered fillets should now be produced with **ASOCRET-M30** exclusively. Due to its water-repellent properties, it offers greater assurance.



#### 1. Covered fillet mortar

Especially suitable as a covered fillet mortar which has no capillary water conductivity. To form a covered fillet in the wall-floor transition as well as internal corners prior to overcoating with structural waterproofing.



#### 2. Blocking render

Impermeable to water from 10 mm and can be applied up to 30 mm as a continuous layer in one application.



#### 3. Smoothing compound

For levelling and smoothing from 3 mm in thickness.



#### 4. Repair mortar

Partially fractured or broken areas and irregularities can be levelled up to 30 mm in one application.

The SCHOMBURG group of companies develops, produces and distributes construction materials systems for the areas of:

- Waterproofing and Restoration
- Tiles/ Natural Stone / Screed installation
- Protective Flooring / Coating Systems
- Concrete Technology

SCHOMBURG is recognised for its development competency and is distinguished both nationally and internationally with over 80 years in the market. System based construction products from its own production plants are held in high esteem throughout the world.

Industry professionals value the level of service provided by the SCHOMBURG Group, along with our large range of high quality products.

In order to stay at the forefront of a continuously advancing market we are always investing in research and development of new and current products. This guarantees high quality products, which in turn leads to customer satisfaction.

SCHOMBURG GmbH & Co. KG

Aquafinstraße 2 - 8

D-32760 Detmold (Germany)

phone +49-52 31-953-00

fax +49-52 31-953-108

email [export@schomburg.de](mailto:export@schomburg.de)

[www.schomburg.com](http://www.schomburg.com)

