



# Declaration of Performance

according Annex III of the Regulation (EU) No. 305/2011

for the product

Soloflex Fast

205439

1. **Unique identification code of the product type:** EN 12004 C2 F
2. **Identification :** batch no.: see packaging of the product
3. **Intended use:** fast hardening, improved cementitious adhesive for internal and external tiling
4. **Manufacturer :** Schomburg GmbH & Co. KG  
Aquafinstraße 2-8  
32760 Detmold
5. **Authorized representative:** not relevant
6. **System or systems of assessment and verification of constancy of performance of the construction product as:** System3  
System 3 reaction to fire
7. **Notified test laboratory:** The notified testing laboratory KIWA Bautest GmbH Dresden identification number 2007 performed the determination of the product-type on the basis of type testing under system 3 and issued: test report No **DD 4217/2011..**  
The notified body MPA NRW identification number 0432 performed the determination of the class regarding reaction to fire on the basis of product testing under system 3 and issued: test report No **230007680-3**
- 8.
9. **Declared performance :**

Essential characteristic	Performance	Harmonised technical specification
Reaction to fire	A1 / A1 <sub>fl</sub>	EN 12004:2007+A1:2012
Bond strength as		
Initial tensile adhesion strength (6h)	≥ 1,0 N/mm <sup>2</sup>	
Adhesion strength after dry storage	≥ 0,5 N/mm <sup>2</sup>	
Durability of bond strength as:		
Tensile adhesion strength after water immersion	≥ 1,0 N/mm <sup>2</sup>	
Tensile adhesion strength after heat ageing	≥ 1,0 N/mm <sup>2</sup>	
Tensile adhesion strength after freeze-	≥ 1,0 N/mm <sup>2</sup>	



Essential characteristic	Performance	Harmonised technical specification
thaw cycles		
Release of dangerous substances	NPD	

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

**Signed for and on behalf of the manufacturer by:**

Wilhelm-Kreyling Dreyer, technician  
(name and function)

Detmold, 02.05.2013

**This declaration of performance was created electronically. It is valid without manual signature.**

The current material safety data sheet and technical data sheet is downloadable under

<http://www.schomburg.de/de/Sicherheitsdatenblatt-datenblaetter.html>

or

[http://www.schomburg.de/de/Technisches\\_Merkblatt-datenblaetter.html](http://www.schomburg.de/de/Technisches_Merkblatt-datenblaetter.html)