

P79-Aufbrennsperre

Priming underneath plaster



Material number	Contents	Unit of quantity	Packaging	Colour
205402002	25	KG	Canister	Red
205402005	210	KG	Drum	Red

Product features

- concentrate
- Non film forming
- hydrophobic

Advantages

Rapid drying

Areas of application

- For absorbent substrates to be plastered (e.g. brick, sand-lime brick and aerated concrete masonry)
- For interior

Technical Data

Material properties

Product components	1 component system
Base material	Fatty acid mixture
Consistency	Liquid
Density (spec. weight)	approx. 1 g/cm ³

Application

Substrate/application temperature	from 5 °C to 30 °C
Consumption	approx. 30.00 - 60.00 g / m ²

P79-Aufbrennsperre

Material consumption

Material consumption rate according to the area of application

Substrate	Dosing
Brick masonry,	1:2- 1:6
Sand-lime brick masonry	1:6
Aerated concrete masonry (gas concrete)	1:2- 1:4

Application technology

Aids/tools

- Brush
- Colour roller
- Primer brush
- Pressure spray system
- Clean mixing bucket

Manual processing

- Applicable with a brush
- Sprayable with pressure spray device

Substrate preparation

Requirement for substrate

1. Dry
2. Load-bearing
3. Free of adhesion inhibiting substances

Usage

Application

1. Dilute P79-Aufbrennsperre with clean water in accordance with the instructions.
2. Apply P79-Aufbrennsperre with suitable tool.
3. P79-Aufbrennsperre must be completely dry before further work can be done on the primed surfaces.

Storage conditions

Storage

Store in a frost-free, cool and dry place. At min. 5 - 40 °C for 36 months in the original canister. Promptly use opened canister.

Disposal

Product leftovers can be disposed of in accordance with disposal code AW 07 01 99.

Notes

- Protect surfaces that are not to be treated from the effects of P79-Aufbrennsperre!
- Do not work wet on wet.
- A site trial is required prior to application (e.g. if the substrate cannot be accurately assessed).
- Clean splashes immediately with water. Glass, metals, window frames etc. can be attacked by P79-Aufbrennsperre.
- Glass, metals, clinker, window frames, etc. can be etched by P79 burn-on barrier.
- Avoid contact with eyes and skin.

GISCODE: M-GP01

The rights of the buyer with regard to the quality of our materials are based on our terms and conditions of sale and delivery. Our technical advice team will be happy to advise you in the case of requirements that exceed the scope of the application described here. In order to be binding, a legally binding written confirmation is required. The product description does not release the user from a duty of care. Lay a test area in the event of uncertainty. This version becomes invalid in the event of a new version being issued.