



Technical Data Sheet

BLANKOL-0

Universal release and impregnation agent

Art.-No. 4 06101

Fields of Application:

BLANKOL-0 has been especially designed for use in precast productions but also for use on job sites. BLANKOL-0 is also well suited for the impregnation of wooden production pallets for paver block machines. It can be applied on all absorbing and non-absorbing large-sized formwork, even when pre-heated up to + 60° C.

Properties and Benefits:

BLANKOL-0 is a solvent-free and odour-neutral release agent which does not lead to build-ups. BLANKOL-0 reduces swelling and embrittlement of wooden formwork/moulds. Production equipment or moulds from steel are usually protected against the formation of new rust. Rust stains on concrete surfaces are so prevented.

Technical Data:

Colour:	yellowish
Form:	liquid
Density:	0.89 g/cm ³
Storage:	not frost sensitive, in closed containers.
Shelf-life:	24 months in closed original containers
Packaging:	1000 l IBCs 210 l drums 25 l kegs

Consumption:

15 - 50 g/m²
Depending on the type of mould.

Instructions for Use:

BLANKOL-0 is to be applied evenly and as thin as possible onto the clean and dry mould. After spraying, drain off with a mineral oil resistant squeegee if necessary.

Special Advice:

- Suitability tests should be carried out prior to usage.
- Avoid puddles!
- Excessive coating can lead to incrustations and build-ups
- Heated moulds up to maximum + 60° C!
- BLANKOL-0 cannot be diluted with water.
- Excess material can be removed with a foam rubber squeegee resistant to mineral oils.

Safety Advice:

Please adhere to the European Safety Data Sheet (MSDS)!