



## Technical Data Sheet

# INDU-ConductiveStrip

## Conductive (earthing) strip

Art.-No. 2 03534

### Properties:

INDU-ConductiveStrip is a single-sided copper foil:

- self-adhesive
- electrically conducting

### Areas of application:

INDU-ConductiveStrip and INDU-ConductiveStrip-AL are used to create a secure connection between horizontal conducting areas and earthing (potential equalisation).

INDU-ConductiveStrip is used within the conductive coating system INDUFLOOR-IB-GWS3 and in the polyurea based system GEPOTECH-12/24.

### Method of application:

Bond the INDU-ConductiveStrip to the professionally pre-prepared and primed substrate at a grid of max. 5 x 5 m (dependent on the room geometry): pull the protective cover from adhesive, place the strip on the substrate and firmly press down. Avoid folds and voids. At the wall / floor junction, bond the INDU-ConductiveStrip as banners with a length of approx. 1.0 m.

Subsequently completely overcoat the area laid with INDU-ConductiveStrip with the conductive lacquer INDUFLOOR-IB2115. Follow the instructions in the INDUFLOOR-IB2115 technical data sheet.

### Note:

The copper strip is to be connected on site to the earthing conductor (potential equalisation).

### Storage:

18 months when stored cool and dry in the original unopened packaging, above +10° C up to 40° C.

### Packaging:

20 m roll/25 rolls per box

### Advice:

- Processing temperatures between +5° C and +35° C.
- Applications that are not clearly explained in this technical data sheet may only be carried out after consultation with and written confirmation from the Technical Services Department of SCHOMBURG.